



GLC 2200 Controller

Compact and Versatile for all Automatic Lubrication Systems



A great design to ensure your equipment is lubricated properly

- Compact design
- User-friendly control panel
- Visual and audible alarm

PROVEN QUALITY. LEADING TECHNOLOGY.



Control for Your Investment

You spend a lot on your equipment. The GLC 2200 controller helps protect components by alerting you to lube event failures and low lubrication levels. You have peace of mind knowing your investment is being protected.

Intelligent Feedback

Choose the rugged GLC 2200 controller for in-cab monitoring of any 9-30 VDC system.



External Mounting Tabs

Easy to mount without having to open the control box.

Monitoring LEDs

LEDs let you know what your system is doing at a glance.

Digital Readout

Easy to read digital display makes it simple to program and monitor your equipment.

Visual and Audible Alarms

In-cab visual and audible alarms let the operator know your equipment needs attention. Or set up a remote audible alarm to alert service or maintenance staff.

Intuitive Control

Simple icon based push buttons make programming easy.


Plug and Play

Colour coded wiring harness with flying leads and easy-to-follow wiring diagrams makes installations efficient.

Actual size shown

Ordering Information

24N468	GLC 2200 Controller
24P314	GLC 2200 Wiring Harness (1.5 m with flying leads)
24P686	GLC 2200 Connector (1) and pins (12)
24P687	GLC 2200 Connectors (5) and pins (60)
16T671	Crimper



24P686



24P314



16T671

GRACO BVBA Industrieterrein Oude Bunders
Slakweidestraat 31 • B-3630 Maasmechelen
Tel: +32 (89) 770 700 • Fax: +32 (89) 770 777
E-mail: info@graco.be • http://www.graco.com

©2012 Graco BVBA 340969ENEU Rev. A 12/12 Printed in Europe.
All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

TECHNICAL SPECIFICATIONS

Physical Dimensions	70 mm wide x 140 mm high x 35 mm deep (2.75 in. wide x 5.53 in. high x 1.38 in. deep)
Protection Grade	IP54
Operating Temperature	-40° C to 80° C (-40° F to 176° F)
Power Source	DC 9-30 VDC